


F1500AS/AE

LOW LIFT AGV

SPECIFICATION

F1500AS/AE is an autonomous low-lift	
device with support and a lifting height up	-
to 1.5 m. It offers flexibility, scalability and	1
360° safety and protection.	r

It can be equipped with contactless, induction, and maintenance-free charging with a fast start and short charging times. Support legs on the sides increase stability when handling wide pallets.



AS AE Туре Fork support Extended fork support Max. pallet size (L, W, H in mm) Width up to 1,400, 1,800x2,300x1,500 length up to 1,500 Navigation Contour **Direction of drive** Forward, backward, on the spot rotation Minimal turning radius (m) Depending on the pallet Max speed (m/s) Forward: 2.0, backward: 0,5 Load capacity (kg) 1,500 Lift Hydraulic Max lift (mm) 1,500 Dimensions from (L, W, H in mm) 2,391x900x2,489 Forks Welded/forged Manipulation From static part, from the ground **Batteries** Lithium Charging Automatic - wireless/contact Control Manual control - touchscreen. Universal remote control (URC) Safety scanners SICK 360°

5G TECHNOLOGY

COMPATIBLE

CE CERTIFIED

Asseco CEIT offers a comprehensive **automatic logistics system**, **including AGV equipment**, **peripherals and our own Twiserion Fleet Manager with VDA 5050 standard** for guiding and monitoring logistics equipment in real time.

WIRELESS

CHARGING

